



Wood Finishing Products
A Division of Farwest Paint Mfg. Co.

SPECIFICATION SHEET

Benite AquaSeal

Product:21500

Pre-Stain / Wood Conditioner

11/2016

DESCRIPTION:

Daly's **Benite AquaSeal** is a clear, penetrating pre-stain sealer and wood conditioner that hardens and protects the wood grain. It does not leave a surface film, is practically odorless and has very little environmental impact. AquaSeal is an excellent pre-stain sealer for most stains, oil or water based. It can also be used to protect wood from weather damage before construction by minimizing water absorption.

RECOMMENDED USES:

INTERIOR - Sand wood with 120 grit sandpaper following the grain, remove dust, apply with roller, brush, spray or dip. Allow to dry 2 - 4 hours depending on the conditions. Benite AquaSeal will raise the grain of the wood slightly, so if staining or finishing over AquaSeal sand lightly with 150 or 220 grit sandpaper to a smooth surface before proceeding to the next step.

EXTERIOR - Apply a full flooding coat. Do not stack treated wood until dry. Apply in temperatures from 40-90° F.

SURFACE PREPARATION: Surface should be free of dust and moisture.

APPLICATION: Brush, roller, spray or most any applicator.

CLEAN UP: Clean tools and brushes with water and a little soap.

THINNING: Not recommended. Product is ready to use as packaged.

COVERAGE:

150 to 200 square feet per gallon on rough surfaces, and 400 to 500 square feet per gallon over smooth wood surfaces.

DRY TIME: Allow 2-4 hours for dry time. Temperature and humidity can affect the dry time so if you have concerns allow longer time before recoat.

V.O.C.: <50 grams per liter.

CAUTIONS:

USE ONLY WITH ADEQUATE VENTILATION.

Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. KEEP OUT OF REACH OF CHILDREN. READ ALL CAUTIONS PRIOR TO USING. KEEP FROM FREEZING. **ENVIRONMENTALLY FRIENDLY.**

Daly's Wood Finishing Products

4522 S 133rd St, Tukwila, WA 98168

www.dalyswoodfinishes.com

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691