



Wood Finishing Products
A Division of Farwest Paint Mfg. Co.

SPECIFICATION SHEET

Seafin Teak Cleaner

Product:1574

11/2018

DESCRIPTION:

Daly's **Seafin Teak Cleaner** is a one-part cleaner for restoring weathered teak prior to applying a new finish.

RECOMMENDED USES:

Daly's **Seafin Teak Cleaner** is for use on exterior teak decks, brightwork and railings.

RECOMMENDED SYSTEMS:

Dilute one part **Seafin Teak Cleaner** with two parts water in a plastic container. Apply diluted solution using synthetic bristle or fiber scrub brush. Allow to set for 3-5 minutes then scrub with grain of wood using stiff fiber scrub brush. Rinse thoroughly with fresh water. Let dry and repeat if necessary. To bring out the natural wood color, use Daly's Oxalic Acid. Mix as per instructions. Apply with a synthetic bristle brush, let set for 5 minutes, but do not let it dry. Rinse with fresh water. After the teak has been restored and is dry, sand and apply one of Daly's Marine Finishes.

COVERAGE: 3 quarts of mix will cover approximately 150 sq.ft.

CLEAN UP: Clean tools and equipment with water. Surfaces such as ladders and walk-ways may become slippery, therefore, rinse with water immediately to avoid safety hazards.

FIRST AID:

If swallowed, call physician immediately. DO NOT INDUCE VOMITING. Give water or milk to drink. In case of eye contact, flush eyes immediately with water for 15 minutes.

In case of skin contact, wash thoroughly with soap and water. If irritation persists, seek medical aid.

WEIGHT PER GALLON: 8.8 lb

FLASH: Non-flammable

V.O.C.: None

CAUTIONS:

CORROSIVE! Harmful or fatal if swallowed. Irritant to eyes and skin. Do not take internally. Wear proper protective clothing such as goggles, rubber or plastic gloves. Close container after each use. NEVER MIX WITH OTHER CHEMICALS, CLEANERS OR DETERGENTS as mixture may release harmful gases. **KEEP OUT OF REACH OF CHILDREN.**

SPECIAL INSTRUCTIONS:

DO NOT FREEZE. However, if product is frozen, allow to thaw at room temperature; do not force thaw. Seafin Teak Cleaner is not a paint remover. For problem areas, a stronger solution may be mixed using 1 part Seafin Teak Cleaner to 1 part water, then follow directions. Seafin Teak Cleaner may be applied to damp surfaces, but not a wet surface. Always test on a small, hidden area first, to be sure of desired results. If splashed on surfaces other than wood, rinse immediately with water.

REGULATORY: Request Safety Data Sheet for pertinent information.