



SPECIFICATION SHEET

Daly's Waterborne Wood Stain

Product:20000

11/2018

DESCRIPTION:

Daly's **Waterborne Wood Stain** is a penetrating, fade resisting, pigmented stain, containing no measurable environmentally harmful organic solvents.

RECOMMENDED USES:

Use on all interior wood surfaces such as furniture, paneling, cabinets, doors and trim. It is not recommended for floors.

RECOMMENDED SYSTEMS:

Stir well before and while using. Surface must be dry, clean and smooth. Wear gloves to keep product from the skin.

APPLICATION: Sand with wood grain using 120 grit sandpaper, finishing with 220 grit. Remove all sanding dust. **DO NOT USE STEEL WOOL.** Apply Daly's Waterborne Wood Stain with a synthetic bristle brush, foam brush, rag or staining pad. Wipe with wood grain to desired tone in 1-3 minutes using a rag damp with stain.

FINAL FINISH: Let stain dry a minimum of 4-6 hours prior to applying one of Daly's finishes, following the instructions for application.

NOTES: To avoid grain raise and spottiness on soft woods such as pine, fir and hemlock apply Daly's Benite or Aquaseal prior to staining. Do not stop in middle of surface area when applying, stain to the edge. If a lap should appear re-wet with a little stain and wipe to a uniform color. Apply two thin coats rather than one heavy coat. Let dry 2 hours between coats. Use a Wood Filler prior to staining if filling is required. Color may vary due to wood or application technique. Test on a small hidden area prior to application.

COLORS & TINTING:

Comes in Daly's standard colors that can be intermixed for additional colors. If tinting is required, up to 4 ounces per gallon of universal colorants may be added. Always test first for compatibility and desired effect. Heavy tint loads may affect dry times.

SURFACE PREPARATION: All surfaces to be finished must be free of loose dirt, dust, other contaminants and must be dry.

APPLICATION: Synthetic bristle brush, foam brush, rag or staining pad.

THINNING: Do not thin.

CLEAN UP: Soap and water.

COVERAGE: Approximately 400 to 500 square feet per gallon.

DRY TIME: 3 to 6 hours. Temperature, humidity and ventilation will effect dry time.

CAUTIONS:

USE WITH ADEQUATE VENTILATION. Do not take internally. Close container after each use. If spraying, use and approved NIOSH/MSHA respirator. **KEEP FROM FREEZING.**

First Aid: If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

VEHICLE TYPE: Alkyd Emulsion / Acrylic Resin Mixture

WEIGHT PER GALLON: 8.6 to 9.3 pounds per gallon

% SOLIDS: 16% to 20% by volume, 18% to 23% by weight

FLASH: Product is non-flammable

V.O.C.: <50 grams per liter.

FLASH: 35 to 45 seconds #2 Zahn Cup.

REGULATORY: Request Safety Data Sheet for pertinent information.

Daly's Wood Finishing Products

4522 S 133rd St, Tukwila, WA 98168

www.dalyswoodfinishes.com

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691