



## Wood Finishing Products

### EZ

Product:

# Clear Wood Finishing System

11/19/12

## SPECIFICATION SHEET

<b>DESCRIPTION:</b>	Daly's <b>EZ</b> Wood Finishing System is a simple solution to recoating all sorts of wood surfaces that might need a fresh, durable, clear refinish coating. Use <b>EZ Clean</b> to prepare the surface for finishing, removing contaminants that may affect adhesion of the topcoat. It will remove grease, dirt and many stains, leaving a wood surface ready to be finished. <b>EZ Fin</b> is a tough, urethane based wood finish that is easy to apply and will give years of new life to wood surfaces.
<b>RECOMMENDED USES:</b>	Daly's <b>EZ</b> Wood Finishing System is designed to give new life to most clear wood surfaces. Use on doors, cabinets, furniture, trim and more. It can be used to repair some blemishes on wood flooring. It can bring new life to exterior wood furniture. Almost anything made of wood can receive a new life. It is intended primarily for previously coated surfaces - for bare wood use other Daly's products such as Daly's AquaSpar.
<b>RECOMMENDED SYSTEMS:</b>	Daly's <b>EZ</b> Wood Finishing System works well over most coated surfaces. It can coat wood and other durable materials such as linoleum, cork, rubber floors and some plastics. It can be used to repair defects on hardwood, prefinished hardwood flooring and laminates. Test the products before use to ensure compatibility. <b>EZ Clean</b> is an excellent all-purpose cleaner and can be used for multiple cleaning tasks as well.
<b>APPLICATION:</b>	We recommend 3-4 thin coats of <b>EZ Fin</b> to most previously finished surfaces. Rough surfaces should be sanded lightly before finishing and the dust removed. Spray or pour <b>EZ Clean</b> to the surface and give a minute for it to attack the dirt. Wipe off with clean rags. Reapply if all contaminants are not fully removed. Wipe off well and allow the surface to dry. When dry, you're ready to finish. Shake or stir <b>EZ Fin</b> well to ensure it is mixed. Try not to over-shake as that may entrap air into the coating. Apply a thin coat by spray, brush, foam brush or lint-free rag. Do not leave puddles. Wait 30 - 60 minutes between coats. recoat until you have a smooth, tough finish for your wood surfaces.
<b>CLEAN UP:</b>	Clean tools and equipment with water immediately after use. <b>EZ Clean</b> may help the clean up process.
<b>COLORS &amp; TINTING:</b>	<b>EZ Fin</b> may be tinted lightly to touch up blemishes, especially on prefinished hardwood flooring. Only tint part of your container, leaving some clear for the finishing coat.
<b>THINNING:</b>	Thinning is not recommended.
<b>SURFACE PREPARATION:</b>	All surfaces should be clean and free of loose dirt, dust and other contaminants before finishing. <b>EZ Clean</b> will remove most contaminants. Some stains may remain and may need other procedures to remove. Daly's Oxalic Acid may help remove stains and should be used according to its specs.
<b>APPLICATION:</b>	<b>EZ Clean</b> by spray or pouring onto surface, a scotch-brite pad may help remove tough contaminants. <b>EZ Fin</b> by brush, pad or spray.

**DRY TIME:** Temperature, humidity and ventilation can affect dry time, 30-60 minutes dry time between coats, 24 hours before use.

**COVERAGE:** 400-500 sq.ft. per gallon, depending on surface texture.

**% SOLIDS:** EZ Fin is 17-18% by weight

**WEIGHT PER GAL:** 8.5 lbs

**VEHICLE TYPE:** EZ Clean - Surfactant and Detergent Blend, EZ FIN - Aqueous Polyurethane Resin Mixture

**FLASH:** N/A Product is water-based.

**V.O.C.:** Maximum 250 gr/L

**CAUTIONS:** **USE ONLY WITH ADEQUATE VENTILATION.**  
Do not take internally. Close container after each use.  
**KEEP OUT OF REACH OF CHILDREN**  
**RESPIRATOR: A NIOSH APPROVED RESPIRATOR MUST BE WORN IF PRODUCT IS TO BE SPRAY APPLIED.**  
Avoid Contact with eyes, skin and clothing. Wash thoroughly after handling.

**FIRST AID:** If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin contact, wash thoroughly with soap and water.

**NOTES:** If spilled, contain EZ Fin and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.  
Apply at temperatures between 45-90 degrees F. Always test for compatibility before use.

**REGULATORY:** Request Material Safety Data Sheet for information pertinent to EPA SARA Title II, Section 313 Supplier Notification and California Proposition 65 Reporting Requirements.

## Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565