



SPECIFICATION SHEET

BenMatte™ Natural Tung-Oil Finish

Product: 13000

3/2017

DESCRIPTION:

Daly's **BenMatte™ Natural Tung-Oil Finish** penetrates into the wood structure, producing the beauty of a low sheen, oil rubbed finish with the added protection of synthetic resins. **BenMatte** is durable and easy to apply, resistant to fading and damage by water, alcohol, scratches and abrasions.

RECOMMENDED USES:

All interior wood surfaces such as cabinets, paneling, millwork, doors and furniture.

RECOMMENDED SYSTEMS:

Natural Unstained Wood - The surface should be clean, dry and smooth. Sand if necessary with 120 sandpaper and remove dust. Apply a liberal coat and allow to set for up to 5 minutes for maximum penetration. While still wet with **BenMatte**, sand with #400 wet/dry sandpaper until smooth feel is produced. Remove excess with a dry absorbent rag. Allow to dry 4 to 6 hours. A second or third coat is recommended for added protection. The additional coats should be wiped on with a rag, sanding is usually not necessary after the first coat. As many coats as desired may be used.

Use Over Daly's Wood Stain - First, be sure to allow the stain coat to set and dry well before attempting to apply **BenMatte** - at least 24 to 48 hours. Second, wipe or brush on a liberal coat of **BenMatte**, allow to set for about 5 minutes then wipe gently to remove the excess using a light touch while wiping. BE SURE NOT TO SAND THIS COAT. Allow to dry 4 to 6 hours before applying an additional coat. Up to six coats may be added for maximum protection.

COLORS & TINTING:

Tinting not recommended. If a stain is desired, see instructions for the use of Daly's Wood Stain.

THINNING: Not recommended. Product is ready to use as packaged.

CLEAN UP: Paint thinner (Mineral spirits).

APPLICATION: Brush, roller or wipe on.

COVERAGE:

200 to 400 sq. ft. per gallon depending on surface texture and dryness. Additional coats: 500 to 600 sq. ft. per gallon.

DRY TIME: 4 to 6 hours between coats. 24 to 48 hours ready to use.

MAINTENANCE: If surface becomes or looks dry, apply **BenMatte** or Daly's LemOil with a soft rag and wipe dry.

STORAGE: Pour unused product into smaller containers or add clean marbles into the opened container to raise the liquid level to eliminate air.

CAUTIONS:

DANGER - CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

Notice: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

SPECIAL INSTRUCTIONS:

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

DISPOSAL OF OILY RAGS: To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.

VEHICLE TYPE: Tung Oil Modified Resin.

WEIGHT PER GALLON: 6.9 pounds per gallon

% SOLIDS: 30% by volume

FLASH: 107°F

V.O.C.: Maximum 550 grams per liter.

Daly's Wood Finishing Products

4522 S 133rd St, Tukwila, WA 98168

www.dalyswoodfinishes.com

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691