



## SPECIFICATION SHEET

### ProFin Gloss™

Product: 1565 Series

1/2017

#### **DESCRIPTION:**

**ProFin™** is a hard-drying, quick setting oil finish that is easy to apply and is exceptionally durable. **ProFin** produces a professional finish, and is often used where spraying is not practical.

#### **RECOMMENDED USES:**

**ProFin** is recommended for wood surfaces such as furniture, cabinets, doors, millwork and paneling. **ProFin** can be used on reasonably protected exterior surfaces such as doors. **ProFin** is compatible with Daly's Wood Stain, as well as most other interior stains. Always test for compatibility prior to finishing.

#### **RECOMMENDED SYSTEMS:**

**Stir well before and while using.** **ProFin** can be applied in a variety of ways. The following guide is to be regarded as a set of suggestions on application. Most application systems will be finalized by the user. Surface must be dry and free of dust, lint, oils or wax. Use of a tack cloth prior to application of each coat is recommended. If applying over stain, be sure the stain is completely dry. Temperature, humidity and ventilation can affect drying time. Apply **ProFin** evenly to a properly prepared surface. Allow to dry 4 to 8 hours. Apply the following coats in the same manner. 2 to 3 coats usually provides an attractive, durable finish. Sanding lightly between coats with fine sandpaper or finishing pad will produce a finer finish. **ProFin** may be wet sanded with 400 wet/dry sandpaper on first coat while still wet for a smoother finish. Wipe to an even wet sheen and allow to dry. Apply subsequent coats as per directions. If applying over a stained surface do not wet sand. If more build and greater depth is desired, on last coat apply an even wet coat and let dry. For a finer finish, **ProFin** may be rubbed down with 4/0 steel wool or a rubbing pad. Do not use steel wool when using **ProFin** on an exterior surface.

#### **COLORS & TINTING:**

Tinting not recommended. If a stain is desired, see instructions for the use of Daly's Wood Stain.

**THINNING:** Not recommended. Product is ready to use as packaged.

**CLEAN UP:** Paint thinner (Mineral spirits).

**APPLICATION:** Lint free rag, brush or foam applicator.

#### **COVERAGE:**

400 to 500 square feet per gallon depending on surface texture and dryness.

**DRY TIME:** Allow 4-8 hours dry time. Temperature and humidity can affect dry time.

**STORAGE:** Pour unused product into smaller containers or add clean marbles into the opened container to raise the liquid level to eliminate air.

**CAUTIONS:**

**DANGER - CONTAINS PETROLEUM DISTILLATE.** VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.

**Notice:** Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**PRECAUTIONS:** Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.

**USE ONLY WITH ADEQUATE VENTILATION.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

**KEEP OUT OF REACH OF CHILDREN.**

**WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**SPECIAL INSTRUCTIONS:**

**IF SPILLED:** Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**DISPOSAL OF OILY RAGS:** To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed, metal container.

**VEHICLE TYPE:** Oil Modified Urethane.

**WEIGHT PER GALLON:** 7.2 pounds per gallon

**% SOLIDS:** 30% by volume

**FLASH:** 107°F Seta Flash Closed Cup

**V.O.C.:**Maximum 550 grams per liter.

**Daly's Wood Finishing Products**

4522 S 133rd St, Tukwila, WA 98168

[www.dalyswoodfinishes.com](http://www.dalyswoodfinishes.com)

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691