



Wood Finishing Products
A Division of Farwest Paint Mfg. Co.

SPECIFICATION SHEET

Seafin AquaSpar™

Product: 155X, 156X

Gloss & Satin

11/2016

DESCRIPTION:

Daly's **SeaFin AquaSpar** is a clear, protective, waterborne polyurethane, containing UVA (Ultraviolet Light Absorber). **AquaSpar** is non-flammable, contains no petroleum distillates, and forms a durable, non-toxic finish.

RECOMMENDED USES:

SeaFin AquaSpar is designed for marine and exterior surfaces such as boats, patio furniture, doors or almost any wood surface where a clear, durable finish is desired. **SeaFin AquaSpar** with UVA offers excellent protection from the exterior elements such as sun, salt air, and water, and is also resistant to boiling water, hot lubricating oils, caustic soda, ammonia and most household cleaners. **SeaFin AquaSpar** may be applied over Daly's Benite and Wood Stains. It is not recommended for exterior wood decks.

RECOMMENDED SYSTEMS:

STIR THOROUGHLY BEFORE USE. **AquaSpar** can be applied using a high-quality synthetic bristle brush or sponge painting pad. Surface should be free of dust, grease, oil, wax and any other foreign matter. Sanding should be done prior to and between coats both on new and old surfaces. Use a damp rag to remove sanding dust prior to application of varnish. For best results, 3 to 4 coats of varnish is recommended. Testing for compatibility with other coatings and surfaces prior to application is strongly recommended.

NEW WORK: Apply 2 or 3 coats full strength as required for protection. Re-coat when surface shows signs of wear. Sand between coats with 220 grit or finer sandpaper.

OLD WORK: If previously varnished surface is in good condition, clean to remove dirt and grime, then sand and varnish. If old finish is not in good condition, remove it and proceed as with new work.

CLEAN UP: Clean up tools and equipment with water immediately after use. Toxic or flammable solvents are not required.

COLORS & TINTING: Tinting is not recommended.

THINNING: Not recommended. Product is ready to use as packaged.

SURFACE PREPARATION: All surfaces to be finished must be free of loose dirt, dust and other contaminants and must be dry.

APPLICATION: Brush, roller or sponge pad.

COVERAGE: 400 to 500 sq.ft. per gallon, depending on surface texture.

DRY TIME: Temperature and humidity can affect dry time. 30-60 minutes dry to touch. 4-24 hours to re-coat. 18-24 hours ready to use, depending on conditions.

CAUTIONS CONTINUED:

USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

SPECIAL INSTRUCTIONS:

SeaFin AquaSpar, like traditional varnishes, will yellow slightly on aging. Weather conditions or sudden drops in temperature will affect any varnish. Do not apply before morning dew has dried, and stop well before dusk. Apply at temperatures between 45° and 90° F.

SeaFin AquaSpar is not recommended for use over non-drying oil stains, water-soluble dye stains, solvent-based sanding sealers or products containing metallic stearates.

% SOLIDS: 25% by volume

WEIGHT PER GALLON: 8.7lbs

VEHICLE TYPE: Aqueous Polyurethane Resin Mixture.

FLASH: Non-flammable

V.O.C.: Maximum 391 grams per liter.

REGULATORY:

Request Material Safety Data Sheet for pertinent information on EPA SARA Title III Section 313 Supplier Notification & California Proposition 65.

Daly's Wood Finishing Products

4522 S 133rd St, Tukwila, WA 98168

www.dalyswoodfinishes.com

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691