



Wood Finishing Products  
A Division of Farwest Paint Mfg. Co.

## SPECIFICATION SHEET

# Wood Brightener

Product:16161

2/2016

### DESCRIPTION:

Daly's **Wood Brightener** is formulated for use on all unfinished or weathered wood surfaces, to remove discoloration, rust stains and make old wood look new. It is ideal as the final step following the use of Daly's DECK & HOUSE CLEANER.

### RECOMMENDED USES:

For use on exterior wood decks, siding, fences, railings, steps and other wood surfaces that need to be brightened.

### RECOMMENDED SYSTEMS:

1. Add 1 part **Wood Brightener** to 4 parts water in a clean, plastic pail or bucket. 5 gallons of mix will cover approximately 800-1000 sq. ft.
2. Apply liberally, using a synthetic bristle brush or pump-type sprayer. Do not apply in direct sunlight or to hot surfaces.
3. Let sit 10-15 minutes. If surface begins to dry, lightly mist with water.
4. Rinse surface thoroughly with water, using a garden hose with nozzle at maximum pressure, or a pressure washer. Repeat procedure if necessary.

**IMPORTANT:** Allow treated surfaces to dry completely before staining or painting.

Do not apply at temperatures below 50°F.

Always test product first on a small, hidden area for compatibility and desired effect.

Protect shrubs: wet with water, cover with plastic. Rinse shrubbery well with hose when job is done.

**CLEAN UP:** Rinse equipment and over-spray areas thoroughly with water. Rinse container and do not reuse.

**WEIGHT PER GALLON:** 8.8 lbx

**FLASH:** Non-flammable

**V.O.C.:** None

### CAUTIONS:

**CAUTION!** Harmful or fatal if swallowed. Use with adequate ventilation. Do not take internally. Wear proper protective clothing such as goggles, rubber or plastic gloves. Close container after each use. **NEVER MIX WITH OTHER CHEMICALS, CLEANERS OR DETERGENTS** as mixture may release harmful gases. **KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

If swallowed, call physician immediately. **DO NOT INDUCE VOMITING.** Give water or milk to drink.  
In case of eye contact, flush eyes immediately with water.  
In case of skin contact, wash thoroughly with soap and water.

**SPECIAL INSTRUCTIONS:**

**DO NOT FREEZE.** However, if product is frozen, allow to thaw at room temperature; do not force thaw.

For removing dirt, mold, algae, mildew and, in some cases, deteriorated stains, use Daly's **DECK & HOUSE CLEANER** prior to using **Wood Brightener**. May be applied to a damp surface, but not a wet surface. If a water-based coating is to be applied over the surface treated with **Wood Brightener**, apply Daly's **OXALIC ACID NEUTRALIZER** to ensure any residual acid is neutralized.

For re-staining decks, use Daly's **DECKSTAIN**.

When applying and rinsing Daly's **Wood Brightener**, surfaces such as ladders, scaffolding, and walking areas may become slippery. Rinse thoroughly to remove from such surfaces. Avoid contact with other surfaces. If contact does occur, rinse immediately with water.

**Daly's Wood Finishing Products**

4522 S 133rd St, Tukwila, WA 98168

[www.dalyswoodfinishes.com](http://www.dalyswoodfinishes.com)

phone(206) 244-8844

toll free(800) 727-9694

fax(206) 246-7691